

Contact MMA Offshore

capacity to support cargo transportation scopes.

Australia

Head Office

Level 10 12-14 The Esplanade Perth WA 6000

Ph: +61 8 9431 7431 Fax: +61 8 9431 7432

South East Asia

Singapore Office

9 Raffles Place, #15-02 Republic Plaza Singapore 048619

Ph: +65 6265 1010 Fax: +65 6864 5555

United Kingdom

Aberdeen Office

30 Abercrombie Court Prospect Road, Arnhall Business Park Westhill Aberdeenshire United Kingdom AB32 6FE

Ph: +44 1224 659950 Fax: +44 1224 659951

MMA Pride

Multipurpose Support Vessel



General		Dimensions	
Official No	398092	LOA	78 m
Call Sign	9V6693	Breadth - moulded	20.4 m
IMO No	9651917	Depth - moulded	7 m
Year Built	2013	Draft	5.39 m
Port of Registry	Singapore	GRT	4,227 T
Flag	Singapore	NRT	1,268 T
Class	American Bureau of Shipping	Deadweight	2,966 T
	 A 1, Offshore Support	Free Deck Area	650 m ²
Notation	Vessel (Supply), *AMS, SPS, *ACCU, *DPS-2, SPS 2008 Unrestricted Service	Deck Strength	5 T/m²

MMAOFFSHORE.COM

MMA Pride

Multipurpose Support Vessel



Performance		
BHP	BHP	5,150
Speed - Maximum	Knots	11.5
Speed - Economical	Knots	10
•		

Tank Capacity		
Fuel Oil	m³	1,018
Fresh Water	m³	702
Foam	m ³	NA
Ballast Water	m³	2,440
Grey Water	m³	23.6
-		
Discharge Rates		

Fresh Water Ballast / Drill Water	60 m³/hr @ 40 m head 60 m³/hr @ 40 m head
Potable Water	60 m³/hr @ 40 m head
Machinery / Propulsion	
Main Engine	2 x 2,575 BHP, Caterpillar

, , , , , , , , , , , , , , , , , , , ,	
Main Engine	2 x 2,575 BHP, Caterpillar 3516C DITA
Bow Thruster	2 x 515 kW, Kawasaki KT-72B3
Stern Thruster	2 x 515 kW, Kawasaki KT-72B3
Generators	4 x 470 kW, Volvo Pents D16 NG HE
Shaft Generator	2 x 1,200 kW Stamford
Emergency Generator	1 x 99 kW
Propulsion	2 x CPP

Deck Equipment	
	1 x 50mt @ 46m /
Deck Crane	15mt @ 50m Liebherr BOS 4200-50
Aux Deck Crane	1 x TTS Marine GPT80-2-14
Capstan	2 x MacGregor HUW 10 UR 400 (5T @ 0-15m/min)
Tugger Winch	2 x 10 tonne MacGregor 14BG253- 4AAQ61
Wire Capacity	22 mm x 200 m
Brake Holding	15 T
Mooring Anchor	4 x Flipper
Weight	4,000 kg
Mooring Wire - Diameter	38 mm
Mooring Wire - Length	1,500 m
Deck Voltage & Sockets	5 x 220 V, 5 x 440 V

Rescue & Fire Fighting	
FRC	Harding FRB 650 15 person capacity x 160 H.P.
Life Boat / Davit	2 x Vanguard 75 person
Life Rafts	2 x 20 men
FiFi Class	NA
Oil Dispersant Boom	NA

Dynamic Positioning	
DP Model	DP2 (Kongsberg DPS 2)
DGPS	x 2
Fanbeam	1 x CyScan + 3 targets 1 x RADius + 2 targets
Accommodation	
	O±v.

Accommodation	
	Qty
Cabin (4 Berth)	112
Cabin (2 Berth)	26
Cabin (Single Berth)	10
Total Accommodation	148 pax

Other Specialist Equipment	
Sewage Treatment Unit	1
Water Maker	2 x 25,000 litres/day Reverse Osmosis

Communication Equipment	
	Qty
Navtex Receiver	1
AIS	1
Watch Alarm	1
SSB	1
Intercom	1
Inmarsat-C	2
EPIRB	1
GMDSS VHF Radio (MF/HF)	4 x VHF, 1 x MF/HF
GMDSS Handheld VHF	3

Navigation Equipment	
	Qty
Magnetic Compass	1
Gyro Compass c/w Autopilot	1
GPS Navigator	1
Radar	1 x X-Band, 1 x S-Band
Speed Log	1

